



IN THE CLAIMS:

Please amend claims 1-6, 8-24, 29, and 30 as follows.

1. (Currently Amended) A method, comprising: for
~~supporting~~ establishing a communication session ~~of~~ between a user equipment
associated with a first access network, ~~by a communication system comprising at least~~
~~one entity between said user equipment and a node~~ of a communication system with
~~which the user equipment is arranged to establish a session via a second network and at~~
least one entity of said communication system between said user equipment and said
node; ~~the method comprising the steps of:~~

a) ~~establishing said session between the user equipment and the node via said~~
~~at least one entity;~~

b) ~~putting the session on hold;~~

e) ~~reserving resources for said session while said session is on hold; and~~

d) ~~resuming said session with a message by which an access network charging~~
identifier is distributed within the second network, wherein the first access network is
different from the second network.

2. (Currently Amended) The method as claimed in claim 1, further
comprising: ~~the step of~~

determining if charging information is provided during the establishment of said
session and carrying out ~~steps b)~~ the putting of the session on hold to the resuming of said

~~session to d)~~ only when it has been determined that the charging information has not been provided.

3. (Currently Amended) A method, comprising: for
~~supporting a modifying an existing communication session of between~~ user
equipment associated with a first access network, ~~by means of a communication system~~
~~comprising at least one entity between said user equipment and a node of a~~
~~communication system with which the user equipment is arranged to establish a session~~
via a second network and at least one entity of said communication system between said
user equipment and said node; ~~the method comprising the steps of:~~

a) ~~— modifying an existing session between the user equipment and the node via~~
~~said at least one entity;~~

b) ~~— putting the session on hold;~~

e) ~~— reserving resources for the modified session while said session is on hold;~~

and

d) ~~— resuming said session with a message by which an access network charging~~
identifier is distributed within the second network, wherein the first access network is
different from the second network.

4. (Currently Amended) The method as claimed in claim 3, further
comprising ~~the step of~~ determining if charging information is provided during the

modifying of said session and carrying out the putting of the session on hold to the resuming of said session ~~steps b) to d)~~ only when it has been determined that the charging information has not been provided

5. (Currently Amended) The method as claimed in claim 1, wherein the establishing ~~step~~ of said session comprises using Session Initiation Protocol (SIP) for said session.

6. (Currently Amended) The method as claimed in claim 1, wherein the establishing ~~step~~ of said session comprises operating at least part of said communication system in accordance with Universal Mobile Telecommunications System (UMTS) standard.

7. (Canceled)

8. (Currently Amended) The method as claimed in claim 1, ~~wherein further comprising configuring said charging identifier comprises to comprise~~ at least a general packet radio service charging identifier (GCID).

9. (Currently Amended) The method as claimed claim 1, wherein the distributing of the access network charging identifier ~~step~~ comprises distributing the access network charging identifier provided in a charging vector.

10. (Currently Amended) The method as claimed in claim 9, wherein the distributing of the access network charging identifier ~~step~~ comprises distributing the charging identifier in a charging vector, ~~and~~ wherein said charging vector comprises a P-charging-vector.

11. (Currently Amended) The method as claimed in claim 1, wherein the establishing step comprises establishing a session wherein said at least one entity comprises a gateway general packet radio service support node (GGSN).

12. (Currently Amended) The method as claimed in claim 1, wherein the establishing ~~step~~ of said session comprises establishing a session wherein said at least one entity comprises a proxy call session control function (P-CSCF).

13. (Currently Amended) The method as claimed in claim 1, wherein the establishing of said session ~~step~~ comprises establishing a session wherein said at least one entity comprises a policy decision function (PDF) function.

14. (Currently Amended) A method as claimed in claim 11, wherein the establishing ~~of said session~~ step comprises establishing a session wherein said at least one entity comprises a proxy call session control function (P-CSCF), the method further comprising ~~the step of~~ sending the charging identifier from the GGSN to the P-CSCF.

15. (Currently Amended) The method as claimed in claim 11, wherein the establishing ~~of said session~~ step comprises establishing a session wherein said at least one entity comprises a policy decision function (PDF) function, the method further comprising ~~the step of~~ sending the charging identifier from the GGSN to the PDF.

16. (Currently Amended) The method as claimed in claim 14, wherein the establishing ~~step of~~ said session comprises establishing a session wherein said charging identifier is sent from the GGSN to the P-CSCF in a common open policy service (COPS) message.

17. (Currently Amended) The method as claimed in claim 15, wherein the establishing ~~step of~~ said session comprises establishing a session wherein said charging identifier is sent from the GGSN to the PDF in a common open policy service (COPS) message.

18. (Currently Amended) The method as claimed in claim 1, wherein the establishing ~~step of said session~~ comprises establishing a session wherein said node comprises a user agent server.

19. (Currently Amended) The method claim as claimed in claim 5, wherein the establishing ~~step of said session~~ comprises establishing a session wherein said charging identifier is sent in an INVITE message.

20. (Currently Amended) The method as claimed in claim 1, wherein the establishing ~~step of said session~~ comprises establishing a session wherein said node comprises user equipment.

21. (Currently Amended) A communication system ~~for supporting a communication session of an user equipment associated with a first access network~~, said system comprising:

a user equipment associated with a first access network, wherein the communication system is configured to support a communication session of said user equipment; and

at least one entity between said user equipment and a node with which the user equipment is arranged to establish a session via a second network, the system being ~~arranged~~ configured to establish said session between the user equipment and the node

via said at least one entity, at least one of said node and said user equipment being ~~arranged~~configured to put the session on hold, at least one of said node and said user equipment being ~~arranged~~configured to ~~reserving~~reserve resources for said session while said session is on hold, at least one of said node and said user equipment being ~~arranged~~configured to resume said session with a message by which at least one entity distributes an access network charging identifier within the second network, wherein the first access network is different from the second network.

22. (Currently Amended) A communication system ~~for supporting a communication session of an user equipment associated with a first access network~~, said system comprising:

a user equipment associated with a first access network, wherein the communication system is configured to support a communication session of said user equipment; and

at least one entity between said user equipment and a node with which the user equipment is ~~arranged~~configured to establish a session via a second network, the system being ~~arranged~~configured to modify a session between the user equipment and the node via said at least one entity, at least one of said node and said user equipment being ~~arranged~~configured to put the session on hold, at least one of said node and said user equipment being ~~arranged~~configured to reserving resources for said modified session while said session is on hold, at least one of said node and said user equipment being

~~arranged~~configured to resume said session with a message by which at least one entity distributes an access network charging identifier within the second network, wherein the first access network is different from the second network.

23. (Currently Amended) A communication system ~~comprising at least one entity between user equipment associated with a first access network and a node with which the user equipment is arranged to establish a session via a second network~~, the system comprising:

at least one entity means between user equipment associated with a first access network and a node with which the user equipment is configured to establish a session via a second network;

establishing means for establishing said session between the user equipment and the node via said at least one entity means;

placement means for putting the session on hold;

reserving means for reserving resources for said session while said session is on hold; and

resuming means for resuming said session with a message by which an access network charging identifier is distributed within said second network, wherein the first access network is different from the second network.

24. (Currently Amended) A communication system ~~comprising at least one entity between user equipment associated with a first access network and a node with which the user equipment is arranged to establish a session via a second network~~, the system comprising:

at least one entity means between user equipment associated with a first access network and a node with which the user equipment is configured to establish a session via a second network;

modifying means for modifying an existing session between the user equipment and the node via said at least one entity;

placement means for putting the session on hold;

first reserving means for reserving resources for the modified session while said session is on hold;

second reserving means for reserving resources for the modified session while said session is on hold; and

resuming means for resuming said session with a message by which an access network charging identifier is distributed within said second network, wherein the first access network is different from the second network.

25. (Previously Presented) A network apparatus, comprising:

a network element configured to establish a communication session with a node via a first access network and a second network, said network element is further

configured to put said session on hold, to reserve resources for said session while said session is on hold, and to resume said session with a message by which an access network charging identifier is distributed within the second network, wherein the first access network is different from the second network.

26. (Previously Presented) A network apparatus, comprising:

a network element configured to modify a communication session with a node via a first access network and a second network, said network element is further configured to put the session on hold, to reserve resources for modifying said session while said session is on hold, and to resume said session with a message by which an access network charging identifier is distributed within said second network, wherein the first access network is different from the second network.

27. (Previously Presented) A network apparatus according to claim 25, wherein the network element is a user equipment.

28. (Previously Presented) A network apparatus according to claim 26, wherein the network element is a user equipment.

29. (Currently Amended) A computer program embodied on a computer readable medium for supporting a communication session of user equipment associated

with a first access network, ~~by means of a~~wherein said communication system ~~comprising~~comprises at least one entity between said user equipment and a node with which the user equipment is arranged to establish a session via a second network, the computer program being configured to perform ~~the steps of~~:

a) ~~—modifying an existing~~establishing said session between the user equipment and the node via said at least one entity;

b) ~~—~~putting the session on hold;

c) ~~—~~reserving resources for the modified session while said session is on hold;

and

d) ~~—~~resuming said session with a message by which an access network charging identifier is distributed within the second network, wherein the first access network is different from the second network.

30. (Currently Amended) A computer program embodied on a computer readable medium for supporting a communication session of user equipment associated with a first access network, ~~by means of a~~wherein said communication system ~~comprising~~comprises at least one entity between said user equipment and a node with which the user equipment is arranged to establish a session via a second network, the computer program being configured to perform ~~the steps of~~:

a) ~~—~~modifying an existing session between the user equipment and the node via said at least one entity;

b)——putting the session on hold;

e)——reserving resources for the modified session while said session is on hold;

and

d)——resuming said session with a message by which an access network charging identifier is distributed within the second network, wherein the first access network is different from the second network.

31. (Previously Presented) A network element for establishing a communication session with a node via a first access network and a second network, said network element comprising:

means for putting said session on hold;

means for reserving resources for said session while said session is on hold; and

means for resuming said session with a message by which an access network charging identifier is distributed within the second network, wherein the first access network is different from the second network.

32. (Previously Presented) A network element for modifying a communication session with a node via a first access network and a second network, said network element comprising:

means for putting the session on hold;

means for reserving resources for modifying said session while said session is on hold; and

means for resuming said session with a message by which an access network charging identifier is distributed within said second network, wherein the first access network is different from the second network.